SECTION 08371 - MIRRORED CLOSET DOORS

PART 1 – GENERAL

1.01 <u>DESCRIPTION OF WORK</u>

- A. Extent and location of all mirrored closet doors is indicated on the drawings and in schedules.
- B. Related Work Described Elsewhere:
 - 1. Section 08800 GLAZING
 - 2. Section 06200 FINISH CARPENTRY

1.02 <u>SUBMITTALS</u>

Submit in accordance with Section 01300 - SUBMITTALS AND SUBSTITUTIONS.

- 1. <u>Catalog Cuts / Shop Drawings:</u> Submit catalog cuts and shop drawings of mirrored closet doors to the Architect for approval.
- 2. <u>Samples:</u> Submit samples of all finishes to the Architect for approval.

1.03 WARRANTY

Furnish a written warranty that all work will be free from defects of materials and workmanship for a period of one year from date of final acceptance.

1.04 DELIVERY

Protect doors and frames during shipment and handling to ensure their undamaged arrival at the job site. Store items at job site and protect against damage. Label and number each item for its respective opening.

PART 2 - PRODUCTS

2.01 MIRRORED CLOSET DOORS

Aluminum frame with (white painted / bronze painted / satin anodized finish), bi-pass sliding mirror panels - Series 220.

PART 3 - EXECUTION

3.01 PREPARATION

- A. Verify that openings are prepared with headers and sills level, jambs plumb, correctly sized to receive doors
- B. Commencement of work will indicate acceptance of surfaces as being suitable for this work.

3.02 ERECTION

Prior to installation, Trade Contractor shall examine each opening to receive the door units and ascertain that it is properly prepared to receive his work.

Installation of units shall be in accordance with final approved manufacturer's shop drawings. All Units shall be installed plumb, level and square without bending, twisting, or otherwise distorting unit members.

3.03 CLEANING

Upon completion and acceptance of all work under this section, thoroughly clean all surfaces of aluminum and mirror, using extreme care. Use of abrasives will not be allowed. Surfaces damaged by improper cleaning shall be the responsibility of the Trade Contractor to repair as approved by the Owner or to replace with new.

END OF SECTION